



EXISTING WALL MOUNTED COMMUNICATIONS OUTLET. QUANTITIES AND TYPES OF JACKS AS INDICATED. (TYPICAL)

EXISTING FLUSH FLOOR WALL MOUNTED COMMUNICATIONS/POWER OUTLET. QUANTITIES AND TYPES OF JACKS AS INDICATED. (TYPICAL)

- 9 EXISTING FLUSH FLOOR MOUNTED BOX WITH SPARE CONDUIT.
- 10 CAT 6A CABLE(S) IN 1 1/4" CONDUIT (BELOW SLAB) TO TELECOM ROOM. QUANTITIES OF CABLES TO MATCH QUANTITIES OF OUTLET JACKS. TERMINATE ON NEW CAT 6A PATCH PANEL IN EXISTING EQUIPMENT RACK #2. CUT AND PATCH EXISTING CONCRETE SLAB AS NEEDED FOR INSTALLING CONDUIT.

CAT 6A CABLE(S) CONCEALED ABOVE CEILING TO TELECOM ROOM. QUANTITIES OF CABLES TO MATCH QUANTITIES OF OUTLET JACKS. FOR DATA JACKS, TERMINATE ON NEW CAT 6 PATCH PANEL IN EXISTING EQUIPMENT RACK #2. FOR VOICE JACKS, TERMINATE ON NEW 110 BLOCK. (TYPICAL)

WALL MOUNTED COMMUNICATIONS OUTLET AT 18" ABOVE FINISHED FLOOR TO CENTER UNLESS OTHERWISE NOTED. QUANTITIES AND TYPES OF JACKS AS INDICATED. (TYPICAL)

FLUSH FLOOR MOUNTED COMMUNICATIONS OUTLET. QUANTITIES AND TYPES OF JACKS AS INDICATED. CUT AND PATCH EXISTING CONCRETE SLAB AS NEEDED FOR INSTALLATION. FIELD VERIFY LOCATION. (TYPICAL)

"BISCUIT" TYPE DATA COMMUNICATIONS OUTLET WITH 10' OF CAT 6A SERVICE LOOP CABLES ABOVE CEILING. QUANTITIES OF CAT 6A JACKS AS INDICATED. FOR CONNECTION OF OWNER FURNISHED AND INSTALLED WIRELESS ACCESS POINT TRANSCEIVER. (TYPICAL)